

| | | | |
|------------------------|---------------|--|-------------|
| SECURFIX (4X0,22 MMQ)H | Specification | | 4AX166 |
| | Rev. | | Page 1 of 1 |

Bare copper conductor 7x0,20 mm
 PVC insulation, nominal thickness 0,25 mm, nominal diameter 1,1 mm
 Yellow, green, white, red
 Cores laid up together
 Overall screen of bare copper drain wire 7x0,20 mm, aluminium/polyester tape
 PVC outer sheath, nominal thickness 0,50 mm, white RAL 9010
 Nominal overall diameter 3,75 mm

ELECTRICAL AND PHYSICAL CHARACTERISTICS


| | |
|-----------------------|----------------------|
| Electrical resistance | < 92,0 ohm/km @ 20°C |
| Insulation resistance | > 100 Mohm*km @ 20°C |
| Working voltage Max | : 250 V |

OTHER CHARACTERISTICS

| | |
|----------------------------|--------------|
| Weight | : 23,6 kg/km |
| Bending radius static min. | : 19 mm |
| Working temperature static | : -20/+70 °C |

REFERENCE STANDARDS

IEC 60228, IEC 60332-1

| | | | |
|---|--------|-----------------|--------------------|
|  | Issued | | |
| | T.D. | Checked T.M. | Date 06/12/2007 |