


MC 740P

DISCONTINUED - Replaced by MC 740-PE

Magnetic Contact, Perpendicular Cable, Surface mount, NC

**Technical data**

Installation method	Surface mount
Contact function	Normally Closed (NC)
Approvals	EN 50131-2-6 Grade 2, Class IIIA, INCERT B-582-0013, VdS G 116504, Class B, SBSC 9-216, Class 1/2, F&P, FG
Contact rating	48 VDC / 500 mA / 10 VA
Magnet type	Alnico 5
Mounting on steel	Not recommended
Make distance (wood) mm	37
Make distance (steel) mm	X
Connection	Cable
Housing material	ABS Plastic
Operating temperature range	-40°C - +70°C
Housing protection class	IP 67
Contact dimensions (L x W x H) mm	60 x 14 x 5
Magnet dimensions (L x W x H) mm	60 x 14 x 5
Grade	2



MC 740P is a small and thin magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening.

Both the contact and the magnet part are in a water proof (IP 67) plastic housing. The small and thin format makes it especially easy to install in limited spaces, e.g. on shutters and drawers.

ORDERING INFORMATION

Code	Description
MC 740P	Magnetic contact, surface mount NC, 2 m cable
MC 740P-6	Magnetic contact, surface mount NC, 6 m cable
MC 740P-10	Magnetic contact, surface mount NC, 10 m cable
MC 740P BL	Magnetic contact, surface mount NC, black, 2 m cable
MC 740P A	Magnetic contact, surface mount NC, anthracite, 2 m cable